## *tuco* | Illustra

Data Sheet

# IA-POE-90-U00 & IA-POE-90-U00-EU IEEE 802.3bt Gigabit 90W PoE Injector



#### Key Features

- Supports 10/100/1000Base-T
  (X) for PoE out and Data in
- IEEE 802.3af/at/bt compliant
- Power input 55~57 VDC, injects power up to 90W
- Provides slim size and DIN-rail with IP40 metal mechanism
- Supports operating temperatures from -40 to 75°C (-40 to 167°F)

#### **High-Quality and Powerful**

The IA-POE-90-U00 & IA-POE-90-U00-EU is a next-generation injector which is compliant with IEEE 802.3af/at/bt. With PoE (Power over Ethernet) technology, both data and power to Ethernet-enabled devices run on a standard CAT5 cable. Based on the IEEE 802.3af/at/bt PoE standard, it provides the capability to serve up to 90W on a single port using four pairs of Cat. 5e/ Cat.6 Ethernet cabling.

The IA-POE-90-U00 & IA-POE-90-U00-EU injector flexibly deploys standard and high powered PD devices to transfer data and power simultaneously through one Ethernet cable while reaching distances of up to 100 meters. It supports dual power inputs via a pluggable terminal block or DC jack. DIN-rail and wall-mounting options provide greater ease of installation.





## Specifications

Communications	IA-POE-90-U00	IA-POE-90-U00-EU
Ethernet	10/100/1000Base-T (X)	
Protocol	IEEE 802.3, 802.3u, 802.3x, 802.3af/at/bt, 802.3ab	
Transmission Distance	Ethernet: Up to 100 m	
Transmission Speed	Up to 1000 Mbps	
Interface		
Connectors	DATA IN: RJ45, PoE OUT: RJ45	
LED Indicators	PoE, SYS	
Environmental		
Operating Temperature / Humidity	-40 to 75°C (-40 to 167°F) / 10 to 95% (non-condensing)	
Storage Temperature / Humidity	-40 to 85°C (-40 to 185°F) / 10 to 95% (non-condensing)	
Electrical		
Input Voltage	55~57 VDC (Single input)	
Power Consumption	Max. 95W (Full load PoE)	
Power Output	90W	
Protection	Reverse Polarity	
Mechanical		
Enclosure	IP40, Metal shell with solid mounting kits	
Product dimensions	84 x 80 x 25 mm (3.307" x 3.15" x 0.984")	
Regulatory		
Safety	UL62368	
Emissions	EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6, EN 61000-4-8	
Immunity	EN 55035	
Environment	CE, FCC	

### Ordering information

Model Number	Description	
IA-POE-90-U00	Illustra IEEE 802.3bt Gigabit 90W PoE Injector	
IA-POE-90-U00-EU	Illustra IEEE 802.3bt Gigabit 90W PoE Injector EU	

Specifications are subject to amendment without notification

### **About Johnson Controls**

Johnson Controls is a global diversified technology and multi-industrial leader serving a wide range of customers in more than 150 countries. Our 120,000 employees create intelligent buildings, efficient energy solutions, integrated infrastructure and next generation transportation systems that work seamlessly together to deliver on the promise of smart cities and communities. Our commitment to sustainability dates back to our roots in 1885, with the invention of the first electric room thermostat.

For additional information, please visit www.illustracameras.com follow us on Facebook, Twitter, and LinkedIn.

© 2021 Johnson Controls. All rights reserved. Product offerings and specifications are subject to change without notice. Actual products may vary from photos. Not all products include all features. Availability varies by regions; contact your sales representative.

